
LEGO® Education SPIKE™ Prime Technical Specifications

Technic™ Medium Angular Motor



Hardware name

Technic™ Medium Angular Motor

Description

The motor is designed to function in as both a motor and sensor. With the integrated advanced Rotation Sensor, the motor can report both speed and position. The motor can also sense direct user input measures if the output is rotated by hand.

Key features

- Speed sensor (measures percentage of maximum design speed)
- · Relative position in degrees
- · Absolute position in degrees (-/+ 180 degrees)
- · Crosshole output on one side, rotating disc with crosshole and building interface on the other side
- The motor has a Technic build geometry that allows for versatile building and easy integration into models

Connector type

LEGO® Power Functions 2.0 (LPF2) for connection to LEGO Smarthubs

Wire length

250 mm

Motor output

Voltage range:

Min: 5VMax: 9V

No load:

- Torque: 0 Ncm
- Speed: 185 RPM +/- 15%
- Current consumption: 110mA +/- 15%

Maximum efficiency:

- Torque: 3.5 Ncm
- Speed: 135RPM +/- 15%
- Current consumption: 280mA +/- 15%

Stall:

- Torque: 18 Ncm
- Speed: 0 RPM
- Current consumption: 800mA +/- 15%

All performance data is based on a 7.2V power supply.

Sensor input

Rotation Sensor:

- Resolution: 360 counts per revolution
- Resolution is the number of counts the sensor makes for every full revolution (360 degrees) on the output axle
- Accuracy: ≤+/- 3 degrees
- Accuracy is defined as the tolerances in the sensor combined with the gearbox slack
- Update rate: 100 Hz
- Update rate is defined as the frequency at which a new sensor reading, position, and speed are available

The LEGO® Education SPIKE™ app may not support all hardware features and functionalities.











